

SnapStone® *flexible* GROUT

GROUT HAZE REMOVAL INSTRUCTIONS

SUPPLIES NEEDED:

- Nylon Scrubber Pad
- Rubber Gloves
- Safety Glasses
- Clean, dry terrycloth rags
- Clean grout sponge
- 5-gallon bucket
- Water supply

GROUT HAZE CLEAN-UP:

For SnapStone® Urethane Flexible Grout VIDEO



- Allow the grout to dry for 24 hours after installation.
- If grout haze is present, perform the following steps:
 - ◆ Use a nylon scrubber pad and one of the following household cleaners:
 - **Urethane Grout Cleaner (UGC)**
 - **KrudKutter® Original or Tough Task Remover**
 - ◆ Apply product to scrubber pad and spread over the entire surface of the tile, avoiding grout lines. If product gets in grout lines, remove by wiping with a clean, dry rag.
 - ◆ Allow product to soak for approximately 5 minutes.
 - ◆ Scrub the tile surface vigorously with the scrubber pad to loosen haze, taking care to ensure product does not get into grout lines. If product gets in the grout lines, remove with a clean, dry, terry cloth rag.
 - ◆ Remove product from tile surface with a clean, dry, terry cloth rag.
 - ◆ Rinse affected tile surface area with clean water and a damp sponge.
 - ◆ Repeat process as necessary until grout haze is removed from tile surface.
- DO NOT expose grout to staining agents or household cleaners for at least 7 days.

Questions?

Visit: SnapStone.com

Or call toll-free: 1-877-263-5861

VIDEO View video demonstration on SnapStone.com

For everyday care, please see the Care & Maintenance section of our web site: SnapStone.com